


KATANA[®]

CORDLESS HEAT GUN INSTRUCTION MANUAL

18V CHARGE-ALL



18V
LITHIUM ION

5 YEAR
WARRANTY*

500°C
MAX TEMP

220090

GENERAL POWER TOOL SAFETY WARNINGS

220090



WARNING Read all safety warnings and all instructions. Failure to follow the warnings and instructions may result in electric shock, fire and/or serious injury. Save all warnings and instructions for future reference. The term "power tool" in the warnings refers to your mains-operated (corded) power tool or battery-operated (cordless) power tool.

1) Work area safety

- a) **Keep work area clean and well lit.** Cluttered or dark areas invite accidents.
- b) **Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.** Power tools create sparks which may ignite the dust or fumes.
- c) **Keep children and bystanders away while operating a power tool.** Distractions can cause you to lose control.

2) Electrical safety

- a) **Power tool plugs must match the outlet. Never modify the plug in any way.** Do not use any adapter plugs with earthed (grounded) power tools. Unmodified plugs and matching outlets will reduce risk of electric shock.
- b) **Avoid body contact with earthed or grounded surfaces, such as pipes, radiators, ranges and refrigerators.** There is an increased risk of electric shock if your body is earthed or grounded.
- c) **Do not expose power tools to rain or wet conditions.** Water entering a power tool will increase the risk of electric shock.
- d) **Do not abuse the cord. Never use the cord for carrying, pulling or unplugging the power tool. Keep cord away from heat, oil, sharp edges or moving parts.** Damaged or entangled cords increase the risk of electric shock.
- e) **When operating a power tool outdoors, use an extension cord suitable for outdoor use.** Use of a cord suitable for outdoor use reduces the risk of electric shock.
- f) **If operating a power tool in a damp location is unavoidable, use a residual current device (RCD) protected supply.** Use of an RCD reduces the risk of electric shock.

3) Personal safety

- a) **Stay alert, watch what you are doing and use common sense when operating a power tool.** Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication. A moment of inattention while operating power tools may result in serious personal injury.
- b) **Use personal protective equipment. Always wear eye protection.** Protective equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection used for appropriate conditions will reduce personal injuries.
- c) **Prevent unintentional starting. Ensure the switch is in the off-position before connecting to power source and/or battery pack, picking up or carrying the tool.** Carrying power tools with your finger on the switch or energising power tools that have the switch on invites accidents.
- d) **Remove any adjusting key or wrench before turning the power tool on.** A wrench or a key left attached to a rotating part of the power tool may result in personal injury.
- e) **Do not overreach. Keep proper footing and balance at all times.** This enables better control of the power tool in unexpected situations.
- f) **Dress properly. Do not wear loose clothing or jewellery. Keep your hair, clothing and gloves away from moving parts.** Loose clothes, jewellery or long hair can be caught in moving parts.
- g) **If devices are provided for the connection of dust extraction and collection facilities, ensure these are connected and properly used.** Use of dust collection can reduce dust-related hazards.

4) Power tool use and care

- a) **Do not force the power tool. Use the correct power tool for your application.** The correct power tool will do the job better and safer at the rate for which it was designed.
- b) **Do not use the power tool if the switch does not turn it on and off.** Any power tool that cannot be controlled with the switch is dangerous and must be repaired.
- c) **Disconnect the plug from the power source and/or the battery pack from the power tool before making any adjustments, changing accessories, or storing power tools.** Such preventive safety measures reduce the risk of starting the power tool accidentally.
- d) **Store idle power tools out of the reach of children and do not allow persons unfamiliar with the power tool or these instructions to operate the power tool.** Power tools are dangerous in the hands of untrained users.
- e) **Maintain power tools. Check for misalignment or binding of moving parts,**

breakage of parts and any other condition that may affect the power tool's operation. If damaged, have the power tool repaired before use. Many accidents are caused by poorly maintained power tools.

- f) **Keep cutting tools sharp and clean.** Properly maintained cutting tools with sharp cutting edges are less likely to bind and are easier to control.
 - g) **Use the power tool, accessories and tool bits etc. in accordance with these instructions, taking into account the working conditions and the work to be performed.** Use of the power tool for operations different from those intended could result in a hazardous situation.
- ### 5) Battery tool use and care
- a) **Recharge only with the charger specified by the manufacturer.** A charger that is suitable for one type of battery pack may create a risk of fire when used with another battery pack.
 - b) **Use power tools only with specifically designated battery packs.** Use of any other battery packs may create a risk of injury and fire.
 - c) **When battery pack is not in use, keep it away from other metal objects, like paper clips, coins, keys, nails, screws or other small metal objects, that can make a connection from one terminal to another.** Shorting the battery terminals together may cause burns or a fire.
 - d) **Under abusive conditions, liquid may be ejected from the battery; avoid contact.** If contact accidentally occurs, flush with water. If liquid contacts eyes, additionally seek medical help. Liquid ejected from the battery may cause irritation or burns.
- ### 6) Service
- a) **Have your power tool serviced by a qualified repair person using only identical replacement parts.** This will ensure that the safety of the power tool is maintained.

This appliance is not intended to be used or cleaned by persons with reduced physical, sensory or mental capabilities, or lack of experience or knowledge, unless they have been given instructions concerning the safe use of the appliance by a person legally responsible for their safety. They should be supervised whilst using the appliance.

Children shall not use, clean or play with this appliance, which when not in use should be secured out of their reach.

Do not operate the product in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust. Battery products create sparks which may ignite the dust or fumes. The heat gun may start a fire if appropriate precautions are not taken.

The product is intended for household use only. Keep the heat gun away from rain or water to avoid risks of fire or electric shock. Never use the heat gun in a damp or very wet area.

Do not expose battery products to rain or wet conditions. Water entering a battery product will increase the risk of electric shock.

Do not leave the heat gun unattended while it is operating. Remove the battery pack from the heat gun when it is not in use. Ensure that the heat gun cannot start accidentally. If the heat gun stops while it is in use, disconnect it from the power supply.

The nozzle gets extremely hot. Wear gloves and eye protection.

Do not direct the hot airflow towards people or animals.

Never reduce the hot airflow by blocking or covering the nozzle.

Ensure that the nozzle does not come into contact with materials during or after operation.

Always wear eye protection when stripping paint overhead.

Always keep the heat gun upright or suspend it with the stand supplied.

Never leave the heat gun out in the rain and do not use it on very damp days.

Always allow the heat gun to cool down completely before storing it.

Always store the heat gun in a safe place, out of the reach of children. It is not a toy.

Always concentrate on the job and use common sense when working with the product. Do not use the product when you are tired or taking medication that may make you drowsy.

Always work in a well ventilated area. Flakes and residues of lead-based paints are highly toxic.

Use the product only for its intended use as described in this manual.

If the product is not working properly, has been dropped, damaged, left outdoors or dropped into water, return to your nearest service centre.


SYMBOLS

The rating plate on your tool may show symbols. These represent important information about the product or instructions on its use.

| | | | |
|--|-------------------------------------|--|--|
| | Direct current, DC | | Waste electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your Local Authority or retailer for recycling advice. |
| | Refer to instruction manual/booklet | | |
| | Wear eye protection | | General warning |
| | Regulator compliance mark | | |

KNOW YOUR PRODUCT

220090




SPECIFICATIONS

| | | | |
|------------------------|-------------------------|--|---------------|
| Voltage | 18V d.c. | Air flow | 200 l/min |
| Max temperature | 500°C | Recommended ambient operating temperature | -17°C to 51°C |
| Run time | 17 mins (4.0Ah Battery) | | |

COOL DOWN FUNCTION

When trigger is depressed the automatic cool down function begins. This does not cool down the tip or nozzles, the intended function is to remove excess heat from the internals of the heat gun.

HOW TO INSERT BATTERY ON TOOL



1. ALIGN BATTERY RIBS WITH TOOL

2. SLIDE INTO TOOL


3. STOP WHEN YOU HEAR IT CLICK IN PLACE




WARNING

TIP AND ATTACHMENTS GET EXTREMELY HOT DURING AND AFTER USE, ALLOW ADEQUATE COOLING TIME BEFORE TOUCHING

HOW TO INSTALL NOZZLES




1. SLIDE NOZZLE ONTO TIP




HOW TO REMOVE NOZZLES

220090




1. TWIST NOZZLE
RELEASE COLLAR (2)




2. NOZZLE DROPS

HOW TO USE HEAT GUN




1. ENSURE SAFETY

Always wear safety glasses when working with the heat gun. Make sure to secure your hair and any baggy clothes. In appropriate situations make sure you wear ear muffs, a mask or a respiratory mask.




2. KEEP HEAT GUN FROM SURFACE

Avoid holding the heat gun too close to the workpiece, 30cm is the recommended minimum distance



3. OPERATE HEAT GUN

Operate the heat gun by pushing the trigger lock off (4) and then pulling the trigger (5) and waving the heat gun side to side over the workpiece.



4. ALLOW TO COOL

Allow adequate time for the heat gun to cool down after use. When trigger is released, the automatic cool-down function begins. Please note, this does not cool down the tip or nozzles. The intended function is to remove excess heat from the internals of the heat gun.

MAINTENANCE

This power tool normally requires no maintenance; from time to time the ventilation slots on the motor casing should be cleaned out. If the unit should become defective, repair should be performed by an authorized service agent for electric tools.

Avoid using solvents when cleaning plastic parts. Most plastics are susceptible to damage from various types of commercial solvents and may be damaged by their use. Use clean cloths to remove dirt, dust, oil, grease, etc.

Warning!

Do not at any time let brake fluids, gasoline, petroleum based products, penetrating oils, etc., come in contact with plastic parts. Chemicals can damage, weaken or destroy plastic which may result in serious personal injury.

KATANA®

**5 YEAR
WARRANTY***

* Standard 3 year warranty with an additional 2 year warranty available subject to online registration via katanapowertools.com.au. Warranty on this Katana product is given by Kinrome Australia Pty Ltd of 3Lakeview Drive, Caribbean Park, Scoresby, Victoria, Australia (Tel +61 3 9730 7100). If this product has materials or workmanship defects (other than defects caused by abnormal or non warranted use) you can, at your cost, send the product to place of purchase, an authorised Kinrome service agent or one of Kinromes addresses for repair or replacement. Your rights under this warranty are in addition to any other rights you have under the Australian Consumer Law or other applicable laws. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. For further details please visit www.kinrome.com.au or call us. Due to minor changes in design or manufacture, the product you purchase may sometimes differ from the one shown on the packaging.

Australia & Global

www.katanapowertools.com.au
enquiries@katanapowertools.com.au
+61 3 9730 7100

Made to Katana specifications and quality standards in China.

NOT INTENDED FOR TRADE USE